



EV charger



Features:

Datasheet	Model	AC7000-AE -25	ACCCIK -AE-25
Input	Power Supply	1P+N+PE	3P+N+PE
	Rated Voltage	230V AC	400V AC
	Rated Current	32A	16A
	Frequency	50/60Hz	60/60Hz
Output	Output Voltage	230VAC	400 V AC
	Maximum Current	32A	16A
	Rated Power	7kW	11kW
User Interface	Charge Connector	Type 2 cable	
	Cable Length	4m	
	Enclosure	Plastic PC940	
	LED Indicator	Green/Yellow/Red	
	RFID Reader	Ware ISO/IEC 14443 A	
	Start Mode	Plug&Play/RFID card/App	
	Emergency Stop	No	
Communication	WiFi	Yes	
	Bluetooth	Optional	
	OCPP	OCPP1.6 ison(OCPP 2.0 optional)	
Safety	Energy Meter	No	
	RCD	6mA DC	
	Ingress Protection	IP65	
	Impact Protection	IK10	
	Electrical Protection	Over current protection. Residual current protection. Surge protection. Over/Under voltage protection. Over/Under frequency protection. Over temperature protection	
	Certification	CE/CB	
	Certification Standard	EN IEC 61851-1:2019. IEC 61851-1:2017. IEC 62955:2018	
Warranty	2 years		
Environment	Installation	Wall-mount/Pole-mount	
	Work Temperature	-30°C -+50°C	
	Work Humidity	5% - 95%	
	Work Altitude	<2000m	
Package	Product Dimension	328.07*180.73*86.84 mm (H*W*D)	328.07*180.73*86.84mm (H*W*D)
	Package Dimension	430*290*200 mm (L*W*H)	430*290*200 mm (L*W*H)
	Net Weight	3.2kg	3.2kg
	Gross Weight	4.0kg	4.0kg
	External Package	Carton	