

SMART IR AC CONTROLLER

Model: SIR600



MULTILANGUAGE
MANUAL



Quick Guide

SALUS Controls Plc, Units 8-10,
Northfield Business Park,
Forge Way, Parkgate
Rotherham, S60 1SD

SALUS Controls GmbH,
Dieselstrasse 34,
63165 Mülheim am Main,
Germany

UK: tech@salus-tech.com
DE / NL: info@salus-controls.de
FR: technicalsupport@saluscontrols.fr
RO: tehnic@saluscontrols.ro
DK: Support@salus-controls.dk



www.saluscontrols.com

SALUS Controls is a member of the Computime Group
Maintaining a policy of continuous product development SALUS
Controls plc reserves the right to change specifications, design
and materials of products listed in this brochure without prior notice.



V01
11/2025

Introduction

The SIR600 is an innovative remote controller designed to enhance your home comfort by allowing you to easily adjust the temperature of the air conditioning unit. Whether you're seeking a cooler environment in the summer or a warmer atmosphere in the winter, the Smart IR AC Remote Controller provides a seamless and efficient solution. Aimed at providing a more comfortable and convenient living experience. This device integrates cutting-edge technology with user-friendly features, ensuring that you can enjoy the perfect indoor climate effortlessly.


Product Compliance

This product complies with the essential requirements and other relevant provisions of Directives 2014/53/EU and 2011/863/EU. The full text of the EU Declaration of Conformity is available at the following internet address: www.saluslegal.com.


Important safety information

The SIR600 must be installed in compliance with any of the EU's regulation and must be stored in a safe dry area. Use the product the way it was destined to be used. The product was destined for indoor usage. To install and use the device correctly, please read all the instructions in this guide. Do not attempt to disassemble, repair, tamper with, or modify the product. Disconnect your device before cleaning it with a dry cloth.

Overall dimensions



Button functions



Box content



LED status & colours

Factory reset	
Standby mode (before pairing)	
Pairing (add SIR600 to the App)	
Pairing completion	LED OFF
IR Learning	
Change setpoint temperature or mode	



- Solid LED light
 - Blinking LED light

Setting up the device



A USB power adapter for the power supply will be required.




Retrieve the AC unit's IR code from the database.




The device shall be added into the Salus Smart Home system with the connection to the Salus UG gateway via the local WiFi network.


Choosing the right location



When installing your Smart IR AC Remote Controller, it's essential to position the device in a location that ensures effective communication with your air conditioner. Make sure there are no obstructions, such as furniture or walls, that could block the IR signals. Position the device within up to 10 meters of the AC unit for optimal performance. Additionally, it's best to place it away from sources of electromagnetic interference, such as microwaves and routers. Try to position it away from windows where it might be exposed to direct sunlight.



Mounting procedure



App setup and operation


Note: First make sure that you have downloaded the SALUS Premium Lite App from the Google Play or App Store. You will need to follow a few easy steps to create an account.




Important: SALUS Smart Home Gateway is required for the installation of SIR600. Please update the gateway to the latest software version before installing SIR600.




Setting Up the IR remote from the App




Select the **Menu** command from top-right corner to open the menu.




From **Equipment** category we select **All Equipment**.




Here we select
Add new Equipment




In order to prepare the SIR600 for connection, hold the button for 5 seconds.
**The blue LED will blink*




Select **Scan for Smart IR AC Controller** as the connection mode.




If the scanning was successful, the infrared device will be shown and we must select it.




After selecting, we will confirm by choosing **Connect equipment**.




Search and select the brand of the AC device.




Note: Once we have selected the AC brand, we have two options available:




Option A
Program the device by capturing commands from your physical AC remote controller and test the commands to ensure they work correctly.




The indications presented on the screen must be properly followed.




If the IR signal was detected, the following notice will appear on the screen. Press **OK**.




FIRST CODESET
Check if the commands work as shown. If they do, then select **YES**.



SECOND CODESET
Check if the commands work as shown. If they do, select **YES**.




THIRD CODESET
Check if the commands work as shown. If they do, select **YES**.




The following message appears.




SIR's blue LED light will be on.




Option B
Program the device by selecting your AC model or remote control model from the list directly.



From the **AC Model** list, select the model of AC device.




Or select the **Remote Model** list and select the model of AC remote. After selection, select **Next**.



Please note !

If you have obtained the suggestion on the codeset ID from our customer service for your AC unit, please select it directly from the list below.



The following message appears.



SIR's blue LED light will be on.

Setting up the network connection


Note: In order for the IR and gateway to communicate, the WiFi Net work must be configured. If the mobile phone and the gateway are not in the same WiFi network, the application cannot access the properties of the device. After following the previous steps it will require for the selection of the WiFi Network.




Select the desired network from the list.




Provide the password for the selected network and select **Provision**.



Name the new equipment and select **Connect Equipment** to confirm.




Select **Finish** to confirm.



Device has been added and will be shown.

Factory reset



In order to realize a factory reset on your device you must press and hold the power button for 5 seconds.

**Green LED light will stay ON for 5 seconds.*

Technical data

Input	5Vdc 1A by USB-C
Connectivity	WiFi 2.4GHz
AC modes	Auto, Cool, Dry, Fan and Heat (Depending on the AC model)
Swing	Supports only vertical swing and up to 7 positions
Fan Speed	Auto and 1 - 7 (Depending on the AC model)
Storage temperature	-10°C to 50°C, <90% RH
Operating temperature	-0°C to 40°C, 5-90% RH, non-condensing
Dimensions (H x W x D)	68mm x 68mm x 27mm